

# VX-1210

## Rugged HF Manpack Transceiver



- Frequency Coverage :
  - RX: 0.5 ~ 30 MHz in 10 Hz Steps
  - TX: 1.6 ~ 30 MHz
- SSB/ CW, AM, and Data Operating Modes
- 500 Channels
- Three custom-programmable Panel Keys
- Power Output: 20W/5W (J3E / A1A / F1B)  
10W/2.5W (H3E)
- MIL-STD Construction
- Weather Resistant, Rugged Construction
- Battery Status Monitor
- Battery Saver
- Whip Antenna (Optional)
- Goose-neck flexible Whip Antenna (Optional)
- Built-in Antenna Coupler (Optional)
- Collapsible Whip Antenna (Optional)
- Alpha-numeric Labeling of Memories
- Selcall / Telcall built in (Optional)
- Kill system to disable unauthorized use (via Selcall)
- Call Alert / Hailer (Multiple hailing tones available)
- Noise Blanker
- CW Semi-break-in
- Transcript™\* SSB Encryption Unit SC20-455 Available
- Field Programming of Frequencies
- Waterproof telephone-type Speaker / Microphone Handset (Optional)
- Optional two-user Handset Combiner (Optional)
- Transmitter Time-out Timer
- Compact size 7.6"(W) x 2.9"(H) x 10.8"(D)  
(193 x 74 x 274 mm)
- Light weight 7.1 lbs (3.2 kg) w/FNB-66LI Lithium-ion Battery
- PC Programmable

\*Transcript™ is a registered trademark of Transcript International

